



Systemabdichtungsbaustoffe

KAUBIT Aktiengesellschaft • Industriestraße 1 • 49413 Dinklage

Telephone: +49 4443 9669-0 • Telefax: +49 4443 9669-66 • Internet: www.kaubit.de • E-Mail: info@kaubit.de

Kaubit FA Floor Sleeve PEVB

Technical Data Sheet

01.12.2021

Self-adhesive, alkali-resistant and fleece-coated butyl floor sleeve for a permanent sealing of drains in combination with sealing systems under tiles.

Properties:

Kaubit FA Floor Sleeve PEVB is a watertight and alkali-resistant butyl floor sleeve for drains. The sleeve is made of polyethylene foil reinforced with non-woven. This material basis causes an excellent bonding with almost any waterproofing materials used under tiles extending over the entire surface of the sleeve.

Applications:

Kaubit FA Floor Sleeve PEVB is suitable as permanently watertight sealing on wall areas for pipe passages of shower and bathtub water fittings under ceramic coverings. The sleeve is completely embedded into the sealing material.

Technical specifications:

Working temperatures:	+5°C
Temperature resistance:	-40°C -50°C
Colour:	blue
Thickness butyl:	1,2 mm
Total measurements:	370 x 370 mm


Diameter hole: hole on request

Preparation of the substrate:

The substrate must be firm, level and load-bearing and free from oil, grease, dust and other separating layers. Remove adhesion-reducing or loose layers through suitable measures. Sand or very rough surfaces should be primed and smoothed before the sleeve is glued on.

Use:

Remove half of the backing film from the butyl sleeve and press it firmly onto the surface, step by step. Now carefully peel off the second half and press it firmly onto the surface. If the silicone film cannot be removed from the butyl wall sleeve, it must not be pulled any further. The adhering point has to be loosened carefully. The film can only be peeled off further once this has been released. These adhesions can be caused by pressure points in the butyl which can be traced back to incorrect storage. The sleeve must be correctly positioned the first time it is affixed. Correction only works to a limited extent, depending on the subsurface.



For safety reasons, the sleeve must be replaced with a new one. Immediately after gluing, the sleeve can be overworked with the right sealant.

Information on further processing:

Kaubit Floor Sleeve PEVB is absolutely silicone-compatible and alkali-resistant. Solvent-free adhesives and coatings may be applied directly onto the wall sleeve. Before applying further product a compatibility test can be carried out.

Cleaning of tools and equipment:

Tools and soiled areas should be cleaned immediately after use with water.

Storage:

Kaubit FA Floor Sleeve PEVB can be used for a period of at least 24 months when stored in a cool and dry place.

Supplied as:

10 pieces / carton 20 pieces / carton

Further units available on request.

Safety information:

The product is not hazardous as defined in the (German) Hazardous Substances Code.

Disposal:

May be disposed of as building site waste.